General Specifications

■ Main specifications

System Type	Powered subwoofer with a line array speaker
Frequency Response (–10 dB)	37 Hz - 20 kHz
Coverage Angle (Horizontal × Vertical)	170° × 30°
Crossover Frequency	240 Hz
Maximum Output Level (Measured peak, IEC noise@1 m)	125 dB SPL
Power Requirements	110-120 V 60 Hz, 220-240 V 50/60 Hz
Power Consumption	25 W (idle), 91 W (1/8 power)
Dimensions (W × H × D)	System (maximum) 334 × 2,000 × 418 mm
Weight	23.0 kg (39 lbs)

■ Control panel

The number of Mixing Channels	2
Analog Inputs	Mono mic/line × 1, mono line × 1
	LINK IN (MONO)
Effects	MODE (SPEECH/MUSIC/CLUB)
Outputs	LINK OUT (MONO)

■ Amplifier section

Rated Output	Dynamic	1,100 W (Subwoofer: 500 W, Line array speaker: 600 W)

■ Speaker section

Enclosure	Line array speaker: Enclosed
	Subwoofer: Bass-reflex type
Speaker Unit	Line array speaker: 1.5" (3.8 cm) Cone × 10
	Subwoofer: 12" (30 cm) Cone
Dimensions (W × H × D)	Line array speaker: 67 × 582 × 86 mm
	Spacer (each): 67 × 555 × 86 mm
	Subwoofer: 334 × 550 × 418 mm
Weight	Line array speaker: 1.8 kg
	Spacer (each): 0.6 kg
	Subwoofer: 20.0 kg

■ Accessories

Included in the package	Power cord × 1, Dedicated cover × 1, Owner's Manual
Optional accessories	DL-SP1K (dedicated dolly)